

CS ProFlex Mercury

Sanding sheet

:: CHARACTERISTIC

The Carsystem ProFlex Mercury are self-adhesive 1/8 sheets based on film. It is perfectly suited for the manual dry sanding process of dust inclusions and imperfections in the painted surface.

:: APPLICATION

The Carsystem ProFlex Mercury is used as the final sanding step before polishing.

:: PRODUCT DATA

Technical data

Dimensions: 29 x 35mm
Holes: no holes
Material: film
Grit material: corundum
Bonding: special treated corundum integrated in modified resin paper

:: HANDLING

The Carsystem ProFlex Mercury can be processed by hand.
We recommend the following additional products:

- Use in combination with the Carsystem ProFlex Mercury Sanding Block soft - 156.555
- Use in combination with the Carsystem ProFlex Mercury Sanding Block hard - 154.173

:: SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, expect we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery terms and conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE