



Technical Information

Product name	:	MoTip Bumper Spray				
Colour	:	Black	Middle grey	Dark grey	Anthracite	White
Article number	:	04073	04074	04075	04076	04085
Supplier / Producer	:	MOTIP DUPLI B.V.				
		Wolfraamweg 2				
		NL-8471 XC WOLVEGA				
		Telephone number				+31 561 – 69 44 00
		Telefax number				+31 561 – 69 44 31

Product description

High quality bumper spray to repair and embellish plastic bumpers, maintaining the original bumper structure.

Product characteristics

Excellent coverage
Lasting colour and lasting gloss
Scratch free and shock proof
Resistant to chemicals and weather influences
Excellent adhesion
Maintains the original structure of the bumper

Physical and Chemical Characteristics

Contents	:	400 ml
Base	:	Alkyd resin
VOC-content	:	Approximately 84% w/w
Solid content	:	Approximately 16% w/w
Gloss	:	Satin matt
Coverage	:	Two bumpers
Dust dry	:	After 20 to 30 minutes
Tack free	:	After 1 hour
Hardened/Re-sprayable	:	After 24 hours
Heat resistant	:	To 110°C

Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface must be clean, dry and free of grease.

Treatment

The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the bumper spray in several thin layers, till the desired result has been achieved. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.