



Q 70-441

2K Solvent Prefill Spray

Characteristics

70-441 is a 2-component spray can pre-filled with propellant, solvent and hardener for one filling of 2K solvent-based top coats using a suitable filling device.

Filling with a filling unit:

Slightly twist and remove the spray head and fill the can with 100 ml of undiluted paint without hardener additives using the filling unit. We recommend sieving the paint before filling into the filling cap or funnel. Please observe the instructions provided by the equipment manufacturer. Replace the spray head by twisting slightly after filling. Then turn the can upside down and spray 1 - 2 times briefly. This cleans the valve and the riser and guarantees the function. Replace the cap and note the colour code and filling quantity on the can if necessary.

Filling quantity: 100 ml

Physical Characteristics



24 month (pre-gassed can that has not yet been filled with paint)



2004/42/IIB(e)(840)<733

Application



cleaning



shake well for 2 min



Remove the red button from the cap. Turn the can by 180° and fit the button onto the pin.



Turn the can upside down and place on a firm surface. Press the red button with the palm of your hand until it clicks into place.



shake well for 2 min




After shaking the can, test spray and check compatibility with the surface and the colour.



15 cm - 20 cm



2 - 3
60µm



Between the coatings
Before the oven drying

5 min
10 min

Processing conditions



Optimum application at 18° C - 25° C and a relative humidity from 40 - 60 %.



Q 70-441

2K Solvent Prefill Spray

Drying



Ready for polishing: 24 h

Continue

If necessary, polish with conventional polishes

Pot life

Approx. 24 h at 20° C room temperature and a relative humidity of approx. 40 - 50 %.
The processing time depends on the ambient temperature. Higher temperatures reduce the pot life, lower temperatures will prolong it.

Finish



After painting, turn the can upside down and spray the valve until empty.

Important Information



The use of the can filled with paint depends heavily on the filled paint material. The information refers to processing 2K top coats and serves as general recommendations. Please observe the technical information of the paint manufacturer. Do not allow the spray can to stay for longer periods without the spray head as otherwise it may be difficult to attach the spray head. The respective FillClean cap set needs to be ordered separately for filling with the FillClean filling unit.

Storage



Store the product in a ventilated place. Keep away from direct exposure to sunlight.
Keep between +15°C and 25°C.

Safety



For more informations check the safety data sheet.



This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products. Copyright: Q-Company Int. GmbH, all rights reserved.

Version: 25-06-2024