




09940 – ISO-ANTISIL



1000 ml +
10 ml

DESCRIPTION

Anti-silicone solution.

USE

09940 ISO-ANTISIL is a compound avoiding the formation of cratering or fish-eyes, when adding directly to the topcoats in the gun cup in the maximum quantity of 1%.

CHARACTERISTICS

This product becomes effective when carrying out paintworks in environments where silicone particles are suspended in the atmosphere (millionths of milligrams are enough) and settle on the surface to paint; or when carrying out paintworks on surfaces previously treated with silicone-based products (polishes, lubricants, etc.) or when using tools contaminated with silicone substances or with surface-active agents.

APPLICATION

09940 ISO-ANTISIL is specific for 2K topcoats, fillers and clearcoats.
ISO-ANTISIL must be added gradually, in the minimum percentage required. A too great quantity can have an opposite effect than desired.

TECHNICAL DATA SHEET N° 0121-GB
UPDATED 10/2007

All information contained in this data sheet is the result of carefully controlled tests and is correct to the best of Lechler's knowledge at the time of issue. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated and the manner of use is the sole responsibility of the user. FOR PROFESSIONAL USE ONLY.