

MOTIP Freezer

Ord.-no.: 090306

Technical Information



Loosen pressed connections such as crankshafts and fastening materials (screws, bolts and nuts) with MOTIP Freezer. MOTIP Freezer briefly decreases temperature to -50°C to loosen pressed connections and has a precise jet spray.

Quality & properties

- Briefly decreases the temperature to -50°C
- Very effective
- Directed jetspray
- 360° valve

Physical & chemical data

- Base: Propane / butane
- Colourname: no colour
- Smell: Characteristic
- Surfaces: Crankshafts, Fasteners (screws, bolts and nuts)
- Minimum Working Temperature: 10°C
- Maximum Working Temperature: 25°C
- Vapour pressure: 3500/20 bar
- Storage stability: 10 y
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C .
- Before use, shake the aerosol.
- Spray the connection to be treated by repeatedly, briefly pressing the nozzle.
- As a result of the fierce decrease in temperature, the connection can be loosed.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of June 10, 2022 – This release replaces all eventually earlier issued versions.